



Project Vinyl III



Product Information

Class UPEC*			$U_4P_3E_2C_2$
Norm			EN ISO 10582
Usage Classification	ISO 10874	EN 685	23 - 34 - 43
Total Thickness	EN ISO 24346	EN 428	2,00 mm
Wear Layer	EN ISO 24340	EN 429	0,70 mm
Total Weight*	EN ISO 23997	EN 430	2800 g/m ²
Abrasion group	EN 660-2		T Class
Standard width	EN ISO 24341	EN 426	2 - 4 m
Standard length	EN ISO 24341	EN 426	+/- 22 m
Dimensional stability	EN ISO 23999	EN 434	≤ 0,40 %
Light stability*	EN ISO 105 B02		≥ 6 degree
Residual indentation*	EN ISO 24343-1	EN 433	≤ 0,10 mm
Impact sound improvement*	EN ISO 717/2		ΔLw 6 dB
Slip resistance (ramp test with oil)	DIN 51130		R10
Reaction to fire	EN 13501-1		Bfl-s1
Thermal resistance	ISO 8302		0,014 m ² K/W
Walk Noise	NF S 31-074		
Static Electrical Propensity	EN 1815		< 2kV (On concrete)

*Certified Value

Features:



2,00 mm



0,70 mm



6 dB



Residential



Commercial



Certifications:



ISO 9001 - BS 14001
BUREAU VERITAS
Certification

