





ACCESS - NETWORK COLLECTION


Technical Specifications

Construction: Multi-level Loop	Standard Backing: EcoAce-Bac®
Fiber: Voxflor® Certified Nylon	Tile Size: 25 x 100 cm
Gauge: 1/10"	Pile Weight: 22 OZ/yd²
Stitches: 8 per inch	Total Thickness: 7.5 ± 0.5 mm
Area per carton: 6m²	Piece per carton: 24 pieces
Traffic Classification: Commercial - Heavy Duty	Anti-microbial: Ultra Fresh (Available)
Average Pile Height: 4.0 ± 0.5 mm	

Installation Methods



Ashlar



Herringbone

**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications

				
				
Certificate Of Declare		Certificate Of EPD		Certificate Of CRI
DOWNLOAD		DOWNLOAD		DOWNLOAD

Performance Specifications

	Test Code	Standard	Test Result
Flammability Tests			
Radiant Panel	ASTM E 648	≥.45 watt/cm²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
Stability			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
Anti-Static			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
Colour Fastness			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
Wear Tests			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
Generic Tests			
Nylon Carpet with EcoAce-Bac®	GLP No. : 100231		Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)

Warranty

15-year Commercial Limited Warranty [DOWNLOAD](#)

Additional Information

- VOXFLOr uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

Additional Files

Installation Guidelines	Maintenance Guidelines
DOWNLOAD	DOWNLOAD






CONNECTION - NETWORK COLLECTION


Technical Specifications

Construction: Multi-level Loop	Standard Backing: EcoAce-Bac®
Fiber: Voxflor® Certified Nylon	Tile Size: 25 x 100 cm
Gauge: 1/10"	Pile Weight: 23 OZ/yd²
Stitches: 8 per inch	Total Thickness: 7.5 ± 0.5 mm
Area per carton: 6m²	Piece per carton: 24 pieces
Traffic Classification: Commercial - Heavy Duty	Anti-microbial: Ultra Fresh (Available)
Average Pile Height: 4.0 ± 0.5 mm	

Installation Methods



Ashlar



Herringbone

**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications



Declare.

Certificate Of Declare

[DOWNLOAD](#)



Certificate Of EPD

[DOWNLOAD](#)

Certificate Of CRI

[DOWNLOAD](#)

Performance Specifications

	Test Code	Standard	Test Result
Flammability Tests			
Radiant Panel	ASTM E 648	≥.45 watt/cm²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
Stability			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
Anti-Static			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
Colour Fastness			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
Wear Tests			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
Generic Tests			
Nylon Carpet with EcoAce-Bac®	GLP No. : 100231		Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)

Warranty

15-year Commercial Limited Warranty [DOWNLOAD](#)

Additional Information

- VOXFLOOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.


Additional Files

Installation Guidelines

[DOWNLOAD](#)

Maintenance Guidelines

[DOWNLOAD](#)




ROUTE - NETWORK COLLECTION


Technical Specifications

Construction: Multi-level Loop	Standard Backing: EcoAce-Bac®
Fiber: Voxflor® Certified Nylon	Tile Size: 25 x 100 cm
Gauge: 1/10”	Pile Weight: 24 OZ/yd²
Stitches: 8 per inch	Total Thickness: 7.5 ± 0.5 mm
Area per carton: 6m²	Piece per carton: 24 pieces
Traffic Classification: Commercial - Heavy Duty	Anti-microbial: Ultra Fresh (Available)
Average Pile Height: 4.0 ± 0.5 mm	

Installation Methods



Ashlar



Herringbone

**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications

				
				
Certificate Of Declare		Certificate Of EPD		Certificate Of CRI
DOWNLOAD		DOWNLOAD		DOWNLOAD

Performance Specifications

	Test Code	Standard	Test Result
Flammability Tests			
Radiant Panel	ASTM E 648	≥.45 watt/cm²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
Stability			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
Anti-Static			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
Colour Fastness			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
Wear Tests			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
Generic Tests			
Nylon Carpet with EcoAce-Bac®	GLP No. : 100231		Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)

Warranty

15-year Commercial Limited Warranty [DOWNLOAD](#)

Additional Information

- VOXFLOr uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

Additional Files

Installation Guidelines	Maintenance Guidelines
DOWNLOAD	DOWNLOAD

